

Twin Plate Clutch Repair Parts (Previous Types)

Part	Part no.	Code	Price with tax	Price	Qty per car	30000-RS###					Remarks
						RS540	RS590	RS595	RS596	RS630	
Clutch Cover *1	3021A-RS050	—	Discontinued	Discontinued	1	●	●				Pressure: 900kgf (push); with cushioning mechanism
	3021A-RS055	—	Discontinued	Discontinued	1					●	Pressure: 1100kgf (push); with cushioning mechanism
	3021B-RS060	—	Discontinued	Discontinued	1			●			Pressure: 950kgf (pull); with cushioning mechanism
	3021B-RS065	—	Discontinued	Discontinued	1					●	Pressure: 1150kgf (pull); with cushioning mechanism
Clutch Disc *1	30101-RS020	—	Discontinued	Discontinued	1	●					Single damper (old model part)
	30102-RS020	—	Discontinued	Discontinued	1	●					Ring type (old model part)
	3010C-RS040	A	26,250	25,000	2		●	●	●		Twin damper, six-pad
	3010C-RS045	A	28,350	27,000	2					●*2	Twin damper, full ring
Flywheel Bolts *1	12315-RS540	A	147	140	8	●					M10, H=7.0, L=21
	12315-D0210	—	Genuine Nissan part	Genuine Nissan part	8						M10, H=8.0, L=26
	12315-42L11	—	Genuine Nissan part	Genuine Nissan part	6		●	●	●		M12, H=8.0, L=26
	12315-52F00	—	Genuine Nissan part	Genuine Nissan part	8					●	M10, H=6.5, L=24
Flywheel *1	1231C-RS540	—	Discontinued	Discontinued	1	●*3					Crankshaft installation surface thickness B=8.5
	1231C-RS590	—	Discontinued	Discontinued	1		●	●	●		Crankshaft installation surface thickness B=12.0
	1231C-RS630	—	Discontinued	Discontinued	1					●	Crankshaft installation surface thickness B=13.0
Center Plate Set	30125-RS020	—	Discontinued	Discontinued	1	●	●	●	●	●	Old model part
M6 Cap Bolts	30131-RS020	A	420	400	3	●	●	●	●	●	Old model part
M8 Hex Bolts	30132-RS020	A	315	300	9	●	●	●	●	●	Old model part
Clutch Sleeve	30501-0H600	—	Genuine Nissan part	Genuine Nissan part	1	●					Old model part
Release Bearing	30502-45P00	—	Genuine Nissan part	Genuine Nissan part	1	●				●	Old model part
	30502-21000	—	Genuine Nissan part	Genuine Nissan part	1		●				Old model part
	30502-12U00	—	Genuine Nissan part	Genuine Nissan part	1			●	●		Old model part

*1 Although the shape may differ from the old model part, it can be used with no problem.

*2 Always replace a full set of flywheel bolts when exchanging discs.

*3 Always replace a full set of flywheel bolts when exchanging flywheels.