

GT L.S.D. Pro Carbon Application Chart

One year guarantee (only in JAPAN)

Vehicle	Model	Engine	Application	GT L.S.D. Pro Carbon	Price with tax	Price	(Diff type axle)	Final ratio	
				2WAY Part no.					
180SX	RS13	CA18DET	All models	38420-RSC20-C5	220,500	210,000	R200V	4.363	
	RPS13	SR20DET	until Oct. '95(5-hole type) M/T	38420-RSC20-B5	220,500	210,000	R200V	4.083	
			from Oct. '95(6-hole type) M/T	38420-RSC20-C5	220,500	210,000	R200V	4.083	
		A/T	38420-RSC20-D5	220,500	210,000	R200V	3.916		
		SR20DE	from Aug. '96	38420-RSC20-C5	220,500	210,000	R200	4.083	
Silvia	S13 PS13	CA18DE,SR20DE	ABS-, or viscousequipped	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083, 4.363	
		CA18DET	All models				R200V	4.363	
		SR20DET	M/T	38420-RSC20-B5	220,500	210,000	R200V	4.083	
			A/T	38420-RSC20-D5	220,500	210,000	R200V	3.916	
	S14 CS14	SR20DE	HICAS-, or viscousequipped	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083	
		SR20DET	All models	38420-RSC20-D5	220,500	210,000	R200V	3.916	
			M/T	38420-RSC20-C5	220,500	210,000	R200V	4.083	
		S15	SR20DE	All models (includes Autech version)	38420-RSC20-D5	220,500	210,000	R200,R200V,R200H	4.083
		SR20DET	All models	38420-RSC20-D5	220,500	210,000	R200V, R200H	3.916, 3.692	
Skyline	HR32	RB20E	ABS-equipped				R200	4.083	
	H(C)R32	RB20DE	All models	38420-RSC20-C5	220,500	210,000			
	E(C)R32	RB25DE	M/T				R200, R200V	4.363	
	HCR32	RB20DET	2WD	38420-RSC20-B5	220,500	210,000	R200V	4.363	
	HNR32	RB20DET	4WD	38420-RSC20-E	220,500	210,000	R200V	4.375	
	HR33	RB20E	ABS-equipped, Non-viscous	38420-RSC20-C5	220,500	210,000	R200	4.083	
			Viscous-equipped				R200V	4.083	
	E(C)R33	RB25DE	until Jan. '96, A/T, Non-viscous	38420-RSC20-D5	220,500	210,000	R200	3.538	
			from Jan. '96, A/T, Non-viscous	38420-RSC20-C5	220,500	210,000	R200	4.363	
			M/T, Non-viscous				R200	4.363	
			until Apr. '94 (5-hole type)	38420-RSC20-B5	220,500	210,000	R200V	4.363	
			2-door, M/T, viscous-equipped						
			Apr. '94 to Jan. '96 (6-hole type)	38420-RSC20-C5	220,500	210,000	R200V	4.363	
			2-door, M/T, viscous-equipped						
			from Jan. '96, viscous-equipped						
	ENR33	RB25DE	4WD	38420-RSC20-C5	220,500	210,000	R200V	4.363	
	ECR33	RB25DET	Except Active LSD spec.	38420-RSC20-B5	220,500	210,000	R200V	4.111, 4.363	
	R34	RB20DE	All models	38420-RSC20-C5	220,500	210,000	R200, R200V	4.363	
	ER34	RB25DE	2WD, A/T, M-A/T				R200, R200V	4.083	
		RB25DET	2WD, M/T	38420-RSC20-B5	220,500	210,000	R200,R200V,R200H	4.363	
ENR34	RB25DE	4WD	38420-RSC20-C5	220,500	210,000	R200V, R200H	4.111		
CPV35 *1 V35 *1	VQ35DE	M/T,CVT	38420-RSC25-33	231,000	220,000	R200V Reinforced	3.538		
CKV36 *1	VQ37VHR	M/T (until Oct. '10)	38420-RSC25-34	231,000	220,000	R200V Reinforced	3.692		
		M/T (from Oct. '10)	38420-RSC25-35	231,000	220,000	R200V Reinforced	3.692		
Skyline GT-R	BNR32 BCNR33	RB26DETT	Except Active LSD spec.	38420-RSC20-E	220,500	210,000	R200	4.111	
Fairlady Z	Z32	VG30DE	Non-ABS	38420-RSC20-B5	220,500	210,000	R200V	4.083	
	Z33 *1	VQ35DE,VQ35HR *2	M/T	38420-RSC25-33	231,000	220,000	R200V Reinforced	3.538	
	Z34 *1	VQ37VHR	M/T (until Jan. '09)	38420-RSC25-34	231,000	220,000	R200V Reinforced	3.692	
			M/T (from Jan. '09)	38420-RSC25-35	231,000	220,000	R200V Reinforced	3.692	
Cefiro	(C)A31	RB20E	ABS-, or HICASequipped	38420-RSC20-D5	220,500	210,000	R200, R200V	3.916	
		RB20DE	All models	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083, 4.363	
		RB20DET	All models	38420-RSC20-B5	220,500	210,000	R200V	4.363	
Laurel	HC33	RB20E	A/T (until Jan. '91), ABS- equipped Non- viscous Viscous equipped	38420-RSC20-D5	220,500	210,000	R200	3.538, 3.900, 3.916	
	H(C)C33	RB20DE	All models	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083, 4.363	
	SC33	RD28	All models	38420-RSC20-D5	220,500	210,000	R200, R200V	3.692, 3.916	
	HCC33	RB20DET	All models	38420-RSC20-B5	220,500	210,000	R200V	4.363	
	HC34	RB20E	Viscousequipped	38420-RSC20-D5	220,500	210,000	R200V	3.916	
		RB20DE	All models	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083	
	G(C)C34 SC34	RB25DE, RD28	Non- Viscous until Dec. '96, viscous-equipped	38420-RSC20-D5	220,500	210,000	R200	3.538, 3.692, 3.916	
							R200V	3.538, 3.692, 3.916	
	G(C)C34	RB25DE	from Dec. '96, viscous-equipped				R200V	4.363	
		RB25DET	All models	38420-RSC20-C5	220,500	210,000	R200V	4.083	
	GNC34	RB25DE	4WD				R200V	4.363	
	G(C)C35	RB25DET	until Sept. '98				R200V	4.083	
from Sept. '98			38420-RSC20-B5	220,500	210,000	R200V	4.083		
Stagea	WHC34 WGC34	RB20E	until Aug. '97	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083	
		RB20DE	All models						
		RB25DE	All viscous-equippeded + nonviscous from Aug.'97	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083	
		RB25DET	M/T from Aug. '98, viscous-equipped	38420-RSC20-B5	220,500	210,000	R200V	4.083	
	WGNC34	RB25DE	All 4WD				R200V	4.363	
			until Aug. '98, 4WD, A/T	38420-RSC20-C5	220,500	210,000	R200, R200V	4.083	
		RB25DET	from Aug. '98, 4WD, A/T	38420-RSC20-B5	220,500	210,000	R200, R200V	4.083	
			from Aug. '98, 4WD, M/T				R200V	4.111	
		RB26DETT	260RS	38420-RSC20-E	220,500	210,000	R200	4.111	

*1 Because the structure, oil temperature can easily rise, it is recommended that a differential gear oil cooler be installed when used in high-load situations.

*2 Include Fairlady Z Version NISMO Type 380RS. *All codes "A"