


# LSD Repair Parts


## For FF (Mechanical LSD)

Detailed information on LSD for FF type

Model	Part no.	Code	Price with tax	Price	Offset	A dimension	B dimension	Side gear serrations	Pinion mate gear, no.	Ring gear bolt size (number)	Gear ratio range	Part information
RS5F41A	38420-RS251	—	Discontinued	Discontinued	20	82.5	φ 90	φ 22 × 21T	4	M10 × 1.25 (8)	3.590~4.050	1.5WAY



Standard overhaul plate arrangement  
Initial torque: 1 kgf·m (design standard value)



· Plate arrangements in illustration are for right-hand side. Prepare the left-hand side by arranging parts in symmetry with this arrangement.



Number in illustration	Part name	Part no.	Code	Price with tax	Price	Thickness (mm)	Standard no. of units
①	Friction Plate	38432-RS251	A	4,305	4,100	1.6	2
②	Friction Disc	38433-RS210	A	1,050	1,000	1.6	2
	Friction Disc *	38436-RS252	A	4,200	4,000	1.7	
③	Spring Plate	38435-RS210	A	1,050	1,000	1.6	2

\* Friction disc no. 38436-RS252 is a thicker disc for clearance adjustment use. Use it during overhaul, depending on the condition of the case and pressure rings.