


# LSD Repair Parts

## Front R160 (Mechanical LSD)


### Front R160 LSD

Model	Part no.	Code	Price with tax	Price	Offset	A dimension	B dimension	Side gear serrations	Pinion mate gear, no.	Ring gear bolt size (number)	Gear ratio range	Part information
RS5F32A	38420-RS360	-	discontinued	discontinued	32	75	φ 114	φ 26 × 25T	4	M12 × 1.25 (8)	3.827~4.176	1.5WAY

\* This type does not use a circlip (snap ring).



Standard overhaul plate arrangement  
Initial torque: 4kgf·m (design standard value)



\* Plate arrangements in illustration are for right-hand side. Prepare the left-hand side by arranging parts in symmetry with this arrangement.



Number in illustration	Part name	Part no.	Code	Price with tax	Price	Thickness (mm)	Standard no. of units	No. of units for initial torque increase
①	Friction Disc	38433-RS360	A	1,050	1,000	1.55	4	
	Friction Disc *	38433-RS361	A	1,050	1,000	1.65		
	Friction Disc *	38433-RS362	A	1,050	1,000	1.75		
②	Friction Plate	38432-RS360	A	1,050	1,000	1.5	2	
③	Spring Plate	38435-RS360	A	1,050	1,000	1.8		

\* Friction discs 38433-RS361 and 38433-RS362 are thicker discs for clearance adjustment use. Use them during overhaul, depending on the condition of the case and pressure rings.